TITLE

METHOD AND APPARATUS FOR FACSIMILE DATA OUTPUT SORTING

5   CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims priority to Japanese patent application No. JPAP11-314846 filed on November 5, 1999 in the Japanese Patent Office, the entire contents of which are hereby incorporated by reference.

10

BACKGROUND

1. Field

The present invention relates to a method and apparatus for facsimile data output sorting, and more particularly to a

15   method and apparatus for facsimile data output sorting that is capable of effectively handling a plurality of print colors and input sheet trays relative to a single output sheet tray.

20   2. Description of the Related Arts

Conventionally, facsimile apparatuses are equipped with a single output sheet tray to receive all transfer sheets after the reproduction process relative to the facsimile data received from other facsimile machines. Users are required

25   on these facsimile apparatuses to sort the output sheets

stacked in the single output sheet tray after receiving the facsimile data from a number of different senders.

A facsimile apparatus capable of sorting on a sender-to-sender basis is described in Japanese Laid-Open Patent

5   Publication No. 10-264484. In this facsimile apparatus, facsimile data is reproduced on a transfer sheet having a different color or size from one used for the facsimile data previously received. This technique, however, requires an employment of multiple input trays to the facsimile apparatus,

10   for receiving differently-colored or differently-sized transfer sheets. Accordingly, the manufacturing cost of the facsimile apparatus is increased by the installation of the multiple input trays. Moreover, it requires a preparation of a number of differently-colored or differently-sized

15   transfer sheets by the users, which is not convenient at all for the users.

SUMMARY

The present invention provides a novel facsimile

20   apparatus which includes at least one communications mechanism, a printing mechanism, a memory, a transfer sheet selection mechanism, and a processor. The above-mentioned at least one communications mechanism is configured to transmit and receive facsimile image data through a specific

25   facsimile procedure. The printing mechanism is configured

2

to have a plurality of print colors.   The memory stores a data table representing a relationship between the print colors and the communications mechanism.   The transfer sheet selection mechanism is configured to select a type of

5   transfer sheet.   The processor is configured to select one of the print colors in accordance with the data table stored in the memory when the communications mechanism receives facsimile image data and to instruct the printing mechanism to print the received facsimile image data using one of the

10   print colors selected by the processor.

The processor may be configured to select one of the plurality of print colors in accordance with the data table stored in the memory on a basis of a communications mechanism used to receive the facsimile image data.

15   The memory may store a data table representing a relationship between the print colors and identification information for identifying a sender of facsimile image data. In this case, the identification information is included in the received facsimile image data.   The processor may

20   further be configured to select one of the print colors in accordance with the data table stored in the memory on a basis of the identification information.

The communications mechanism may be configured to transmit and receive the facsimile image data through any one

25   of G3 and G4 facsimile procedures.

3

The identification information may be any one of a transmitter terminal identification, a called station identification, and a remote terminal identifier, included in a header of the received facsimile image data.

5   The memory may store a data table representing a relationship among the print colors, the type of transfer sheet, and the communications mechanism, and the processor may be configured to select one of the print colors and the type of transfer sheet in accordance with the data table

10   stored in the memory.

The processor may be configured to select one of the print colors and the type of transfer sheet in accordance with the data table stored in the memory on a basis of a communications mechanism used to receive the facsimile image

15   data.

The memory may store a data table representing a relationship between the print colors, the type of transfer sheet, and identification information for identifying a sender of facsimile image data. In this case, the

20   identification information is included in the received facsimile image data. The processor may further be configured to select one of the print colors and the type of transfer sheet in accordance with the data table stored in the memory on a basis of the identification information.

25   The transfer sheet selection mechanism may be

4

configured to select one of transfer sheet trays and the

memory may store a data table representing a relationship

among the print colors, the one of transfer sheet trays, and

the communications mechanism. The processor may further be

5   configured to select one of the print colors and one of

transfer sheet trays in accordance with the data table stored

in the memory.

The present invention further provides a novel method

of sorting output transfer sheets in a facsimile apparatus.

10   In one example, a novel method includes the steps of storing,

selecting, and printing. The storing step stores a data

table representing a relationship between a plurality of

print colors and at least one communications procedure. The

selecting step selects one of the print colors in accordance

15   with the data table stored in the storing step when the

facsimile apparatus receives facsimile image data through the

communications procedure. The printing step prints the

received facsimile image data in one of print colors selected

in the selecting step.

20   The selecting step may select one of the print colors

in accordance with the data table stored in the storing step

on a basis of the communications procedure used to receive

the facsimile image data.

The storing step may store a data table representing a

25   relationship between the print colors and identification

5

information for identifying a sender of facsimile image data.

In this case, the identification information is included in

the received facsimile image data.   The selecting step may

select one of the print colors in accordance with the data

5   table stored in the storing step on a basis of the

identification information.

The communications procedure may be any one of G3 and

G4 facsimile procedures.

The identification information may be any one of a

10   transmitter terminal identification, a called station

identification, and a remote terminal identifier, included in

a header of the received facsimile image data.

The storing step may store a data table representing a

relationship among the print colors, a type of transfer sheet,

15   and the communications procedure and the selecting step may

select one of the print colors and the type of transfer sheet

in accordance with the data table stored in the storing step.

In this case, the printing step may print the received

facsimile image data in one of the print colors and on the

20   type of transfer sheet both selected in the selecting step.

The selecting step may select one of the print colors

and the type of transfer sheet in accordance with the data

table stored in the storing step on a basis of the

communications procedure used to receive the facsimile image

25   data.

6

The storing step may store a data table representing a relationship between the print colors, the type of transfer sheet, and identification information for identifying a sender of facsimile image data. In this case, the

5   identification information is included in the received facsimile image data. The selecting step may select one of the print colors and the type of transfer sheet in accordance with the data table stored in the storing step on a basis of the identification information.

10   The above-mentioned method may further include a switching step for switching between a plurality of transfer sheet trays. In this case, the storing step may store a data table representing a relationship among the print colors, the transfer sheet trays, and the communications procedure,

15   and the selecting step may select one of the print colors and one of the transfer sheet trays in accordance with the data table stored in the storing step.

BRIEF DESCRIPTION OF THE DRAWINGS

20   A more complete appreciation of the present application and many of the attendant advantages thereof will be readily obtained as the same becomes better understood by reference to the following detailed description when considered in connection with the accompanying drawings, wherein:

25   Fig. 1 is a block diagram of a facsimile apparatus

according to an embodiment of the present invention;

Fig. 2 is a flowchart for explaining an exemplary print color selection operation performed based on a communications procedure by the facsimile apparatus of Fig. 1;

5   Fig. 3 is a data table representing a relationship between sender identifications of facsimile image data and the print colors;

Fig. 4 is a flowchart for explaining another exemplary print color selection operation performed based on the sender

10   identifications by the facsimile apparatus of Fig. 1;

Fig. 5 is a data table representing a relationship between the sender identifications of facsimile image data, the print colors, and input sheet trays; and

Fig. 6 is a flowchart for explaining an exemplary print

15   color and input sheet tray selection operation performed based on the sender identifications by the facsimile apparatus of Fig. 1.

DETAILED DESCRIPTION

20   In describing preferred embodiments illustrated in the drawings, specific terminology is employed for the sake of clarity. However, the invention is not intended to be limited to the specific terminology so selected and it is to be understood that each specific element includes all

25   technical equivalents which operate in a similar manner.

8

Referring now to the drawings, wherein like reference numerals designate identical or corresponding parts throughout the several views, particularly to Fig. 1, a facsimile apparatus 1 according to an embodiment of the present invention is explained. Fig. 1 shows the facsimile apparatus 1 which includes a CPU (central processing unit) 100, a ROM (read only memory) 101, a RAM (random access memory) 102, a page memory (PM) 103, a DCR 104, a printer 105, a G3-CCU-1CH unit 106, a G3-CCU-2CH unit 107, a G4-CCU unit 108, and a system bus 109. By controlling the operations of these components, the CPU 100 controls the entire operations of the facsimile apparatus 1. The components mentioned above are connected to the system bus 109.

The ROM 101 stores a control procedure along which the facsimile apparatus 1 operates and a print color selection procedure which designates numeric numbers corresponding to print colors so that the printer 105 accordingly selects colors using the designated print colors to print an image onto a transfer sheet in accordance with facsimile image data received from other facsimile machines. The RAM 102 temporarily stores data when the CPU 100 processes the data. The PM 103 stores the facsimile image data received.

The DCR 104 returns the received facsimile image data to its original state. The printer 105 prints the received facsimile image data onto the transfer sheet using the colors

designated through the print color selection procedure.

Each of the G3-CCU-1CH unit 106 and the G3-CCU-2CH unit 107

individually controls the operations for transmitting and

receiving facsimile image data through the G3 line. The G4-

5   CCU unit 108 also individually controls the operations for

transmitting and receiving facsimile image data through the

G4 line.

Referring to Figs. 1 and 2, a color change operation of

the facsimile apparatus 1 is explained. In this case, the

10   facsimile apparatus 1 has a plurality of print colors

available for the printing operation performed by the printer

105. The plurality of print colors are assigned to the

communications line types, such as a G3 line, a G4 line, or

the like, on a one-to-one basis. When the facsimile

15   apparatus 1 receives the facsimile image data though the G4

line, for example, it prints an image in the print color

assigned to the G4 line according to the received facsimile

image data.

The ROM 101 stores data representing such assignments

20   of the print colors relative to the communications lines such

as a G3 line, a G4 line, or the like. The facsimile

apparatus 1 has the assignments of the green, blue, and red

colors to the 1 channel of the G3 line, the 2 channel of the

G3 line, and the G4 line, respectively. Accordingly, the

25   printer 105 prints an image in the green color at a receipt

through the G3-CCU-1CH unit 106, in the blue color at a receipt through the G3-CCU-2CH unit 107, and in the red color at a receipt through the G4-CCU unit 108.

Alternatively, the RAM 102 may be configured to store the data representing the assignments of the print colors relative to the communications lines such as the G3 line, the G4 line, or the like. In this case, the users can change the assignments of the print colors to suit their needs or preferences. This user change may conveniently be made through an operation panel (not shown) provided to the facsimile apparatus 1, or may be instructed from a host computer through a network interface (not shown) connecting the host computer and the facsimile apparatus 1.

Fig. 2 shows a flowchart of the color change procedure performed by the facsimile apparatus 1. In Step S200 of Fig. 2, the CPU 100 checks if one of the G3-CCU-1CH unit 106, the G3-CCU-2CH unit 107, and the G4-CCU unit 108 receives the facsimile image data. This check process is kept continued until one of the G3-CCU-1CH unit 106, the G3-CCU-2CH unit 107, and the G4-CCU unit 108 receives the facsimile image data. If one of the G3-CCU-1CH unit 106, the G3-CCU-2CH unit 107, and the G4-CCU unit 108 receives the facsimile image data and the check result of Step S200 is YES, the facsimile apparatus 1 then determines which unit receives the facsimile image data. Before the determination process, the CPU 100 reads

11

an appropriate determination procedure stored in the ROM 101.

In Fig. 201, the CPU 100 determines if the G3-CCU-1CH unit 106 receives the facsimile image data. If the G3-CCU-1CH unit 106 receives the facsimile image data and the check result of Step S201 is YES, the CPU 100 reads the print color selection procedure stored in the ROM 101. In the facsimile apparatus 1, the green color is assigned as a print color for the facsimile image data received through the G3-CCU-1CH unit 106. Accordingly, the CPU 100 instructs the printer 105 in Step S202 to select the green color.

If the G3-CCU-1CH unit 106 receives no facsimile image data and the check result of Step S201 is NO, the process proceeds to Step S203 in which the CPU 100 determines if the G3-CCU-2CH unit 107 receives the facsimile image data. If the G3-CCU-2CH unit 107 receives the facsimile image data and the check result of Step S203 is YES, the CPU 100 reads the print color selection procedure stored in the ROM 101. In the facsimile apparatus 1, the blue color is assigned as a print color for the facsimile image data received through the G3-CCU-2CH unit 107. Accordingly, the CPU 100 instructs the printer 105 in Step S204 to select the blue color.

If the G3-CCU-2CH unit 107 receives no facsimile image data and the check result of Step S203 is NO, the process proceeds to Step S205 in which the CPU 100 determines if the G4-CCU unit 108 receives the facsimile image data. If the

12

G4-CCU unit 108 receives the facsimile image data and the
check result of Step S205 is YES, the CPU 100 reads the print
color selection procedure stored in the ROM 101.   In the
facsimile apparatus 1, the red color is assigned as a print
5   color for the facsimile image data received through the G4-
CCU unit 108.   Accordingly, the CPU 100 instructs the
printer 105 in Step S206 to select the red color.

     If the G4-CCU unit 108 receives no facsimile image data
and the check result of Step S205 is NO, the CPU 100 reads
10   the print color selection procedure stored in the ROM 101.
In the facsimile apparatus 1, the black color is assigned as
a print color for the facsimile image data received through
none of the G3-CCU-1CH unit 106, the G3-CCU-2CH unit 107, and
the G4-CCU unit 108.   Accordingly, the CPU 100 instructs the
15   printer 105 in Step S207 to select the black color.

     After Step S202, S204, S206, or S207, the process
proceeds to Step S208 in which the printer 105 instructs its
engine mechanism (not shown) to use the print color selected
in Step S202, S204, S206, or S207.   Then, in Step S209, the
20   facsimile apparatus 1 supplies a predefined transfer sheet
from a sheet tray (not shown).   In Step S210, the printer
105 reproduces a first page in the selected print color in
accordance with the received facsimile image data on the
transfer sheet supplied in Step S209.   In Step S211, the
25   printed transfer sheet is ejected from the facsimile

13

apparatus 1.   In this operation, the first page of the

received facsimile image data is transferred to the printer

105 from the PM 103.

After a completion of the first page reproduction, the

5   CPU 100 increments the page number for the next reproduction

by 1 in Step S212.   Then, in Step S213, the CPU 100 checks

if a non-printed-page remains in the received facsimile image

data or not.   If a non-printed-page remains in the received

facsimile image data and the check result of Step S213 is NO,

10   the process returns to Step S209 to perform the reproduction

operations for the remaining pages.   If no non-printed-page

remains in the received facsimile image data and the check

result of Step S213 is YES, the process returns to Step S200

to repeat the same procedure as described above.

15   In this way, the facsimile apparatus 1 can reproduce

the images in different print colors in accordance with the

assignments relative to the lines, that is, relative to the

communications control units used.   The users thereby easily

sort the transfer sheets which are stacked in the output tray

20   (not shown) of the facsimile apparatus 1.

Next, another print color selection operation of the

facsimile apparatus 1 is explained with reference to Figs. 3

and 4.   In this case, the facsimile apparatus 1 controls the

print color on the basis of contents of a TTI (transmitter

25   terminal identification) which is information, included in

14

the header of the received facsimile image, for identifying the sender of the facsimile image data. Fig. 3 shows an example of a table representing a relationship between the TTI and the print color. According to this table, "ABC" of

5   TTI corresponds to the red print color, "DEF" of TTI corresponds to the blue print color, and so on for example. That is, when the received facsimile image data includes "ABC" of TTI, for example, the facsimile apparatus 1 selects the red print color to perform the print operation using the

10 red print color, and when the received facsimile image data includes "DEF" of TTI, for example, the facsimile apparatus 1 selects the blue print color to perform the print operation using the blue print color. The table of Fig. 3 may include a plurality of combinations of TTI and different print colors

15 including the above-mentioned examples such as the "ABC" and the red print color and "DEF" and the blue print color. The data of the table shown in Fig. 3 is stored in a non-volatile memory (not shown) such as a NVRAM (non-volatile random access memory), for example.

20   Users may register and alter the combinations of the TTI and the color shown in the table of Fig. 3 through an operation panel (not shown) provided to the facsimile apparatus 1, or may instruct from a host computer through a network interface (not shown) connecting the host computer

25 and the facsimile apparatus 1.

Fig. 4 shows an exemplary procedure of the print color

selection operation based on the TTI information.   In Step

S400, the facsimile apparatus 1 reads the TTI information of

the received facsimile image data.   In Step S401, the CPU

5   100 compares the TTI information to the table of Fig. 3 and

determines if TTI corresponds to ABC.   If TTI corresponds to

ABC and the determination result of Step S401 is YES, the

process proceeds to Step S405 in which the CPU 100 instructs

the printer 105 to select the red print color.   If TTI does

10   not correspond to ABC and the determination result of Step

S401 is NO, the process proceeds to Step S402 for the CPU 100

to again compare the TTI information to the table of Fig. 3

and so as to determine if TTI corresponds to DEF.

If TTI corresponds to DEF and the determination result

15   of Step S402 is YES, the process proceeds to Step S404 in

which the CPU 100 instructs the printer 105 to select the

blue print color.   But, if TTI does not correspond to DEF

and the determination result of Step S402 is NO, the process

proceeds to Step S403 and the CPU 100 instructs the printer

20   105 to select the black print color.

After that, in Step S406, the printer 105 instructs the

print engine to use the print color selected in Step S403,

S404, or S405 to reproduce an image in accordance with the

received facsimile image data.   Then, the print color

25   selection operation ends.

After the print color selection operation, the
facsimile apparatus 1 may reproduce the received facsimile
image data on a transfer sheet using the print color selected
through the print color selection operation, thereby
5   completing the process of receiving the facsimile image
information.

In the way as described above, the facsimile apparatus
1 can reproduce facsimile images in a specific print color
according to the sender of the facsimile image data based on
10   the TTI information included in the header of the received
facsimile image data.   The users thereby easily sort the
transfer sheets stacked in the output tray (not shown)
provided to the facsimile apparatus 1.

Alternatively, the facsimile apparatus 1 can use CSI
15   (called station identification) or RTI (remote terminal
identification) for the above-mentioned purpose instead of
using TTI.

Next, a print color and sheet tray selection operation
of the facsimile apparatus 1 is explained with reference to
20   Figs. 5 and 6.   In this case, the facsimile apparatus 1 has
a plurality of available print colors and a plurality of
transfer sheet trays in each of which a type of transfer
sheets are contained different from others.   With this
configuration, the facsimile apparatus 1 selects the print
25   color and the type of transfer sheet on the basis of contents

of the TTI (transmitter terminal identification) information.
Fig. 5 shows an exemplary table representing a relationship
among the TTI information, the print color, and the sheet
supply tray. According to this table, "ABC" of TTI

5   corresponds to the red print color and the first tray, "DEF"
of TTI corresponds to the red print color and the second tray,
"GHI" of TTI corresponds to the blue print color and the
first tray, "JKL" of TTI corresponds to the blue print color
and the second tray, and so on, for example. That is, when

10   the received facsimile image data includes "ABC" of TTI, for
example, the facsimile apparatus 1 selects the red print
color and the first tray to perform the print operation using
the red print color and the transfer sheet supplied from the
first tray. For another example, when the received

15   facsimile image data includes "DEF" of TTI, for example, the
facsimile apparatus 1 selects the red print color and the
second tray to perform the print operation using the red
print color and the second tray. Further, when the received
facsimile image data includes "GHI" of TTI, for example, the

20   facsimile apparatus 1 selects the blue print color and the
first tray to perform the print operation using the blue
print color and the first tray. Further, when the received
facsimile image data includes "JKL" of TTI, for example, the
facsimile apparatus 1 selects the blue print color and the

25   second tray to perform the print operation using the blue

print color and the second tray.

The table of Fig. 5 may include a plurality of combinations of TTI, the print colors, and the sheet trays including the above-mentioned examples such as the cases of 5 "ABC," "DEF," "DEF," and "JKL." The data of the table shown in Fig. 5 is stored in a non-volatile memory (not shown) such as a NVRAM (non-volatile random access memory), for example.

Users may register and alter the combinations of the TTI, the color, and the sheet tray shown in the table of Fig. 10 5 through an operation panel (not shown) provided to the facsimile apparatus 1, or may instruct from a host computer through a network interface (not shown) connecting the host computer and the facsimile apparatus 1.

Fig. 6 shows an exemplary procedure of the print color 15 selection operation based on the TTI information. In Step S600, the facsimile apparatus 1 reads the TTI information of the received facsimile image data. In Step S601, the CPU 100 compares the TTI information to the table of Fig. 5 and determines if TTI corresponds to ABC. If TTI corresponds to 20 ABC and the determination result of Step S601 is YES, the process proceeds to Step S607 in which the CPU 100 instructs the printer 105 to select the red print color. If TTI does not correspond to ABC and the determination result of Step S601 is NO, the process proceeds to Step S602 for the CPU 100 25 to again compare the TTI information to the table of Fig. 5

and so as to determine if TTI corresponds to DEF.

If TTI corresponds to DEF and the determination result of Step S602 is YES, the process proceeds to Step S607 in which the CPU 100 instructs the printer 105 to select the red print color. But, if TTI does not correspond to DEF and the determination result of Step S602 is NO, the process proceeds to Step S603 for the CPU 100 to again compare the TTI information to the table of Fig. 5 and so as to determine if TTI corresponds to GHI.

If TTI corresponds to GHI and the determination result of Step S603 is YES, the process proceeds to Step S606 in which the CPU 100 instructs the printer 105 to select the blue print color. But, if TTI does not correspond to GHI and the determination result of Step S603 is NO, the process proceeds to Step S604 for the CPU 100 to again compare the TTI information to the table of Fig. 5 and so as to determine if TTI corresponds to JKL.

If TTI corresponds to JKL and the determination result of Step S604 is YES, the process also proceeds to Step S606 in which the CPU 100 instructs the printer 105 to select the blue print color. But, if TTI does not correspond to JKL and the determination result of Step S604 is NO, the process proceeds to Step S605 and the CPU 100 instructs the printer 105 to select the black print color.

After that, in Step S608, the printer 105 instructs the

20

print engine to use the print color selected in Step S605, S606, or S607 to reproduce an image in accordance with the received facsimile image data.

Then, In Step S609, the CPU 100 again compares the TTI information to the table of Fig. 5 and determines if TTI corresponds to ABC. If TTI corresponds to ABC and the determination result of Step S609 is YES, the process proceeds to Step S615 in which the CPU 100 instructs the printer 105 to select the first tray. If TTI does not correspond to ABC and the determination result of Step S609 is NO, the process proceeds to Step S610 for the CPU 100 to again compare the TTI information to the table of Fig. 5 and so as to determine if TTI corresponds to DEF.

If TTI corresponds to DEF and the determination result of Step S610 is YES, the process proceeds to Step S614 in which the CPU 100 instructs the printer 105 to select the second tray. But, if TTI does not correspond to DEF and the determination result of Step S610 is NO, the process proceeds to Step S611 for the CPU 100 to again compare the TTI information to the table of Fig. 5 and so as to determine if TTI corresponds to GHI.

If TTI corresponds to GHI and the determination result of Step S611 is YES, the process proceeds to Step S615 in which the CPU 100 instructs the printer 105 to select the first tray. But, if TTI does not correspond to GHI and the

21

determination result of Step S611 is NO, the process proceeds

to Step S612 for the CPU 100 to again compare the TTI

information to the table of Fig. 5 and so as to determine if

TTI corresponds to JKL.

5   If TTI corresponds to JKL and the determination result

of Step S612 is YES, the process also proceeds to Step S614

in which the CPU 100 instructs the printer 105 to select the

second tray. But, if TTI does not correspond to JKL and the

determination result of Step S612 is NO, the process proceeds

10   to Step S613 and the CPU 100 instructs the printer 105 to

select the first tray. Then, the print color selection

operation ends.

After the above-mentioned print color and sheet tray

selection operation, the facsimile apparatus 1 may reproduce

15   the received facsimile image data on a transfer sheet

supplied from the sheet tray and using the print color both

selected through the print color and sheet tray selection

operation, thereby completing the process of receiving the

facsimile image information.

20   In the way as described above, the facsimile apparatus

1 can reproduce the facsimile images in a specific print

color and on a specific type of transfer sheets according to

the sender of the facsimile image data based on the TTI

information included in the header of the received facsimile

25   image data. The users thereby easily sort the transfer

22

sheets stacked in the output tray (not shown) provided to the facsimile apparatus 1.

Alternatively, the facsimile apparatus 1 can use CSI (called station identification) or RTI (remote terminal

5   identification) for the above-mentioned purpose instead of using TTI.

This invention may be conveniently implemented using a conventional general purpose digital computer programmed according to the teaching of the present specification, as

10   will be apparent to those skilled in the computer art. Appropriate software coding can readily be prepared by skilled programmers based on the teachings of the present disclosure, as will be apparent to those skilled in the software art.   The present invention may also be implemented

15   by the preparation of application specific integrated circuits or by interconnecting an appropriate network of conventional component circuits, as will be readily apparent to those skilled in the art.

Numerous additional modifications and variations of the

20   present application are possible in light of the above teachings.   It is therefore to be understood that within the scope of the appended claims, the present application may be practiced otherwise than as specifically described herein.

23